

# DuraPoly™ Barcode Labels

## Second surface image

- Your high density barcodes will scan with outstanding reliability.
- Achieve permanent adhesion to almost any surface with the option to choose from an extensive selection of 3M® brand permanent acrylic pressure sensitive adhesives.
- Second-surface image for exceptional durability: polyester is printed on the underside of material.



## FEATURES

- Extremely fine resolution of fine high density barcodes, detailed logos and graphics, including halftones.

### Conforms to Industry Standards:

ISO 15416

MIL-DTL-15024F

ISO 15416

ANSI-X3.182-1990

RoHS, WEEE, REACH

as well as other applicable standards.

## BARCODES

- Any barcode symbology may be utilized, including linear or two-dimensional codes. Multiple barcodes and multiple symbologies can be imaged on each part.
- Variable data can be generated from any sequence you specify or in the case of complex or random data you may provide an electronic data file.
- Our rigorous Quality Management System and robust data management services ensure data integrity and complete delivery.

## MATERIALS

- Premium Clear Polyester .004" thick with permanent pressure sensitive adhesive backing available in thickness ranging from .003" to .125".
- A wide variety of premium 3M® brand adhesives is available to provide the optimum bond to your attachment surface.
- Produced in virtually any size or shape.
- Imaging technologies include Photographic, Digital Printing and conventional Screen Printing.

800.382.2323 (toll free)

858.549.8708

858.549.9828

Mail@ExpressCorp.com

ISO 9001:2008 Certified - ITAR Registered

Member: Automatic Identification Manufacturers Association

Member: AIM UID Supplier Alliance

Member: National Assn. of Graphic Identification Product Manufacturers

Member: Specialty Graphic Imaging Association

9155 Trade Place, San Diego, CA 92126 | ExpressCorp.com

  
**EXPRESS**  
IDENTIFICATION MADE SIMPLE